


TECHNICAL SPECIFICATIONS

Quality	: AX
Yarn Fiber	: 100% Solution Dyed Nylon IMPREL FINESSE
Gauge and Structure	: 1 / 10 " Cut pile Machine Tufted
Width	: 4.00M
Pile Weight	: $\pm 38 \text{ oz/yd}^2$ (1300 g/m ²)
Total Weight	: $\pm 2,250 \text{ g/m}^2$
Pile Height	: $\pm 8.0 \text{ mm}$
Total Height	: $\pm 11.0 \text{ mm}$
Tuft Density/M ²	: $\pm 300 \text{ 000}$
Backing	: Twinback
Fire Class	: Cfl-s1 (EN 13501-1) / EN 14041 : 2008-05
Thermal Resistance	: EN 14041 : 2008-05 $\pm 0.14\text{m}^2 \text{ k/W}$
Light Fastness	: EN 14041 : 2008-05 ≥ 7
Water Fastness	: EN 14041 : 2008-05 $\geq 4 - 5$
Electrical Behaviour	: EN 14041 : 2008-05 Antistatic (NPD)
Formaldehyd Emission	: EN 14041 : 2008-05 (NA / HCHO)
Pentachlorophenol	: EN 14041 : 2008-05 (DL / PCP)
Certificate	: GUT (DA02BB62) / CE (DOP : 1011#IE00CV)
Warranty	: Life time Stain safe / Everlasting Softness
Origin	: Made in Belgium

1/10" cut pile	1/10" cut pile	1/10" cut pile	1/10" cut pile
100% solution dyed PA IMPREL® FINESSE	100% solution dyed PA IMPREL® FINESSE	100% solution dyed PA IMPREL® FINESSE	100% solution dyed PA IMPREL® FINESSE
RUG Twinback	DOSSIER Twinback	RÜCKEN Twinback	BACKING Twinback
POOLHOOGTE ± 8 mm	HAUTEUR DU VELOURS ± 8 mm	POLHÖHE ± 8 mm	PILE HEIGHT ± 8 mm
TOTALE HOOGTE ± 11 mm	HAUTEUR TOTALE ± 11 mm	GESAMTHÖHE ± 11 mm	TOTAL HEIGHT ± 11 mm
POOLGEWICHT ± 1.300 g/m ²	POIDS DU VELOURS ± 1.300 g/m ²	POLGEWICHT ± 1.300 g/m ²	PILE WEIGHT ± 1.300 g/m ²
TOTAAL GEWICHT ± 2.250 g/m ²	POIDS TOTAL ± 2.250 g/m ²	GESAMTGEWICHT ± 2.250 g/m ²	TOTAL WEIGHT ± 2.250 g/m ²
AANTAL NOPPEN/M ² ± 300 000	NOMBRE DE POINTS/M ² ± 300 000	NOPPEN/M ² ± 300 000	TUFT DENSITY/M ² ± 300 000
LICHTECHTHEID ≥ 7	RÉSISTANCE À LA LUMIÈRE ≥ 7	LICHTECHTHEIT ≥ 7	LIGHT FASTNESS ≥ 7
WATERECHTHEID ≥ 4-5	RÉSISTANCE À L'EAU ≥ 4-5	WASSERECHTHEIT ≥ 4-5	WATER RESISTANCE ≥ 4-5
WARMTEDOORLAATWEERST. ± 0.14 m ² K/W	RÉSISTANCE THERMIQUE ± 0.14 m ² K/W	WÄRMEDURCHLASSWIDERST. ± 0.14 m ² K/W	THERMAL RESISTANCE ± 0.14 m ² K/W
BRANDKLASSE Cfl-s1 (EN 13501-1) Indien verkleefd	CLASSEMENT FEU Cfl-s1 (EN 13501-1) en pose collée	BRANDKLASSE Cfl-s1 (EN 13501-1) verklebt	FIRE CLASS Cfl-s1 (EN 13501-1) If glued





EN14041




20

Industries - Kanegom-
straat 15 - BE 8700 Tielit
DOP: T011#IE00CV

Textile Floor Covering EH 1307
Notified body 2401

www.pro-dis.info



LIFETIME STAINSAFE
WARRANTY



ETERNAL BLEACH
CLEANABILITY



20 YEARS
WEAR WARRANTY



INFINITE
LIGHT FASTNESS



EVERLASTING
SOFTNESS





DECLARATION OF PERFORMANCE

DOP: 1011#IE00CV

1. Unique identification code of the product-type:

1011#IE00CV

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

WFB - Textile floor covering - pile carpet acc. EN 1307:2014

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Industries NV/Division - Kanegemstraat 15 - B - 8700 Tielt

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).

CRET; Centre de recherches et d'études techniques du tapis Rue du vert bois, Zone industrielle, P.O. Box 30 F - 59531 Neuville-en-Ferrain Cedex

Notified Body





2014/012

certificate of constancy of performance

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not applicable

9. Declared performance


Essential characteristics	Performance	Harmonised technical specification
Reaction to fire		EN 14041:2008-05
Content of Pentachlorophenol		EN 14041:2008-05
Formaldehyd Emissions		EN 14041:2008-05
Slip resistance		EN 14041:2008-05
Electrical behavior (dissipative)	NPD	EN 14041:2008-05
Electrical behavior (conductive)	NPD	EN 14041:2008-05
Electrical behavior (antistatic)	NPD	EN 14041:2008-05
Thermal conductivity [W/mK]	NPD	EN 14041:2008-05
Water-tightness	NPD	EN 14041:2008-05

10. The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer Signed for and on behalf of the manufacturer by:

Luc Jongbloot, Business unit manager
(name and function)

02.04.2020, Tielt
(place and date of issue)


(signature)