

GX-200

CONSTRUCTION SPECIFICATIONS

Construction	Tufted Level Cut Pile
Face Yarn	100% BCF Nylon Fluorine Treated Soil Resistant Yarn
Colour System	Piece Dyed
Gauge X Stitch	1/10" X 14/in.
Yarn Weight	1,100 g/m ² (32 oz/sq. yd)
Pile Height	6mm
Backing Materials	PVC with Built-in Glass Fibre
Total Weight	5.4kg/m ² (Nominal)
Total Thickness	9mm (Nominal)
Module Size	500mm X 500mm
Packing	16 Tiles per Box (4m ²)

PERFORMANCE SPECIFICATIONS

Flame Resistance	Methenamine Pill Test (DCC FF 1-70) 'Passes'
Flooring Radiant Panel	(ASTM E-648) NFPA253-1.1 watts/cm ²
Smoke Chamber Test	(ASTM E-662) NFPA258-Flaming Mode-440
Electrostatic Propensity	(AATCC 134) 1.7KV or Less
Dimensional Stability	(AACHEN) 0.039% Change or Less
Colour Fastness to Water	(AATCC 107) Grade 5
to Ozone	(AATCC 129) Grade 3.5
to Shampoo	(AATCC 138) Grade 5
to Dry Crock	(AATCC 8) Grade 5
to Wet Crock	(AATCC 8) Grade 5

*GX-200 series carpet tiles are recommended to be installed in a quarter-turn (checkered) layout in all areas with the exception of stair installations.
*Custom made colour is available for order more than 300m² per colour.

Production lead time is approximately 30 days after receiving customer's written confirmation of acceptance of the trial colour sample.

材料規格

紗毛型態	簇絨等高切毛纖維
紗質	100%BCF 尼龍
染色方式	片染
隔距 X 針數	1/10 X 14/in.
毛重	1,100g/m ²
毛高	6mm
底基材	聚乙稀樹脂 + 玻璃纖維
總重	5.4kg/m ²
總厚	9mm
尺寸	500mm X 500mm
包裝	16枚 / 箱 (4m ²)

*GX-200 係列塊地毯、縱橫方向鋪法是標準法，不過，橫撈斜向鋪法，橫撈斜角若沒有特別指定也可以用縱橫方向鋪法標準鋪法。

*用戶可從現存色彩中、選取任何一種訂量須超過300m²。
生產所需時間 用戶以重面形式確認接受試辦色樣起計、30天