

TECHNICAL SPECIFICATIONS

Item Name :	Hotel Line (HL)
Quality :	100% PP Stainsafe
Tufted Construction :	Level Cut/Loop-pile
Pile Weight :	± 730 g./m ² (22 oz./Yd ²)
Total Weight :	± 1950 g./m ² (58 oz./Yd ²)
Tufted Pile Height :	± 5.5 mm
Total Height :	± 7.5 mm
Width :	13'-2" (4M)
Primary Backing :	Woven Polypropylene
Secondary Backing :	Action Back
Guage :	5/32"
Number of Tufts/m² :	± 120000

Gala Edition

310	910	640	680
980	780	810	
180	880	840	

Fabricagemethode Getuft 5/32" lussenpool	Méthode de fabrication Tuftée 5/32" poil bouclé	Herstellungsverfahren Getuftet 5/32" Schlingenpool	Manufacturing process Tufting 5/32" Looppile
Pool Samenstelling 100% PP StainSafe®	Composition du velours 100% PP StainSafe®	Polmateriaal 100% PP Fleckweg®	Pile content 100% PP StainSafe®
Tuftdoek Geweven PP	Support Tissé PP	Trägermaterial PP Gewebe	Primary backing Woven PP
Rug Ultratex Quick+ viltrug (1) Synthetische dubbele rug (2)	Dossier feutre Ultratex Quick+ (1) Double dossier synthétique (2)	Rückenausrüstung Ultratex Quick+ Vliesrücken (1) synthetischer Zweitrücken (2)	Secondary backing Ultratex Quick+ feltbacking (1) Synthetic backing (2)
Poolgewicht ca. 730 gr/m ²	Poids du velours ca. 730 gr/m ²	Polgewicht ca. 730 gr/m ²	Pile weight ca. 730 gr/m ²
Totaal gewicht ca. 1.950 gr/m ²	Poids total ca. 1.800 gr/m ²	Gesamtgewicht ca. 1.800 gr/m ²	Total weight ca. 1.800 gr/m ²
Poolhoogte ca. 4,5 mm	Hauteur du poil ca. 4,5 mm	Polhöhe ca. 4,5 mm	Pile height ca. 4,5 mm
Totale hoogte ca. 8 mm (1) ca. 7 mm (2)	Hauteur totale ca. 8 mm (1) ca. 7 mm (2)	Gesamthöhe ca. 8 mm (1) ca. 7 mm (2)	Total height ca. 8 mm (1) ca. 7 mm (2)
Aantal noppen ca. 120.000/m ²	Nombre de points ca. 120.000/m ²	Noppenzahl ca. 120.000/m ²	Number of knots ca. 120.000/m ²
Breedte 400 cm Dessinrapport 22,5 cm W x 27 cm H	Largeur 400 cm Raccord 22,5 cm W x 27 cm H	Breite 400 cm Rapport 22,5 cm W x 27 cm H	Width 400 cm Dessin repeat 22,5 cm W x 27 cm H
Aantal kleuren 10	Nombre de coloris 10	Farbenzahl 10	Number of colours 10
Lichtechtheid 5 - 6	Résistance à la lumière 5 - 6	Lichtechtheid 5 - 6	Light fastness 5 - 6
Waterrechtheid 4 - 5	Résistance à l'eau 4 - 5	Wasserechtheid 4 - 5	Water resistance 4 - 5
Warmteoorlaatweerstand 0,15 m ² K/W (1) 0,14 m ² K/W (2)	Résistance thermique 0,15 m ² K/W (1) 0,14 m ² K/W (2)	Wärmedurchlasswiderstand 0,15 m ² K/W (1) 0,14 m ² K/W (2)	Thermal resistance 0,15 m ² K/W (1) 0,14 m ² K/W (2)
Geluidsisolatie 26 dB (1) 25 dB (2)	Isolation aux bruits d'impact 26 dB (1) 25 dB (2)	Trittschalldämmung 26 dB (1) 25 dB (2)	Sound insulation 26 dB (1) 25 dB (2)
Brandklasse Efl (EN13501-1)	Classement feu Efl (EN13501-1)	Brandverhaltensklasse Efl (EN13501-1)	Fire class Efl (EN13501-1)
Bijzonderheden Bleekmiddelreageert Pool naar binnen	Caractéristiques Résiste à l'eau de Javel Velours à l'intérieur	Besonderheiten Bleichmittelreageert Flor Innen	Characteristics Bleach resistant Pile inside



Onder voorbehoud van wijzigingen der technische specificaties - Sous réserve de modifications techniques - Unter Vorbehalt von Änderungen der technischen Daten - All rights reserved to alter technical specifications. Kijk voor de uitgebreide garantievoorwaarden op www.stain-safe.com - Pour le détail des conditions de garantie, rendez-vous sur www.stain-safe.com - Detaillierte Garantiebedingungen finden Sie auf www.stain-safe.com - For detailed warranty conditions, see www.stain-safe.com

Balta Broadloom
Wakkensteenweg 2, 8710 Sint-Baafs-Vijve • Belgium
T +32 (0)56 62 22 11 • F +32 (0)56 62 23 55 • broadloom@baltagroup.com • www.baltagroup.com


Product properties (EN 1307 REPORT)



name(s) of tested quality: **Gala Edition**
 manufacturer / applicant: **BALTA Industries N.V.**
 PRODIS registration no.: **A453CD4F**

Date: 12.07.2013

Information on basic construction data



basic requirements (table 4): fulfilled type of carpet: 1
 type of manufacture (ref 1): pile carpet acc. EN 1307 - tufted
 type of surface (ref 2): loop pile - loop pile like - patterned
 primary backing (ref 3): woven - PP
 secondary backing (ref 4): textile backing - spunbond - man-made fibres

pile fibre composition: 100% PP

total carpet weight:	1.950 [g/m ²]	surface pile mass:	450 [g/m ²]
total carpet thickness:	8,0 [mm]	surface pile thickness:	4,5 [mm]
thickness of backing:	3,5 [mm]	surface pile density:	0,100 [g/cm ³]
density of backing:	0,429 [g/cm ³]	number of tufts:	1.200 [1/dm ²]

Information on use and luxury classes

appearance retention: 22 testing done on underlay: no
 drum test (short term): ≥ 3,0 (Vettermann 5000 or Hexapod 4000)
 drum test (long term): ≥ 2,5 (Vettermann 22000 or Hexapod 12000)
 wear performance: 4,0 [ITR] (calculated for type 1 carpets)
 - - - [Wi] (calculated for type 2 carpets)

CLASSIFICATION

overall use class:

22+

luxury class:

LC 2

Information on additional characteristics if applicable

suitable on stairs: yes occasional	electrical behaviour antistatic: yes body voltage walking test: 2,0 [kV] vertical resistance: - - - [Ω] - - -
suitable with castor chairs: no - - -	
suitable on underfloor heating: yes thermal resistance: 0,150 [m ² K/W]	acoustical characteristics calculated value or measured average for sound absorption: item [α _w] or [α _s] impact noise improvement: [ΔL _w]
suitable under incidental humid conditions: no	
resistant to fraying: no	
surfacetreatments for antistatic properties: no / flame retardant properties: no / antisoil, antistain properties: no	

Specific information for carpet tiles

not applicable



B R O A D L O O M

Wakkensteenweg 2
B-8710 Sint-Baafs-Vijve
Belgium
Tel. +32 (0)56 62 22 11
Fax +32 (0)56 62 23 55
broadloom@baltagroup.com
www.baltagroup.com

Sint Baafs-Vijve, 17/04/13

FIRE CERTIFICATE

GALA

We hereby confirm that above quality meets the requirements for the **European fire class Efl** according to the Test method EN ISO 9239-1 and EN ISO 11925-2, the standard classes of reaction to fire for floor coverings EN 13501-1 and the regulations in the new CE standard EN 14041

With kind regards,

A handwritten signature in blue ink, appearing to read "Geert Vanden Bossche", with a horizontal line underneath.

Geert VANDEN BOSSCHE
Marketing Director Balta